



Marga Lift

**MARGA PROGRESSIVE SAFETY
GEAR ORDER FORM**

DOC. NO.

R.500.01.EN

DOC. DATE

13/04/2022

ORDER

OFFER REQUEST

TO :

COMPANY :
 ADDRESS :
 FAX NO. :
 CONTACT :

DATE :
 CUSTOMER REF. :
 INSTALLATION NO. :
 REQUESTED DELIVERY DATE :

ORDER QUANTITY

1 2 Pcs.

GUIDE RAIL TYPE (*)

| | | | |
|-------------------------------------|-----------------------------------|-------------------------------------|------------------------------------|
| <input type="checkbox"/> T 70-1 / A | <input type="checkbox"/> T 82 / A | <input type="checkbox"/> LUBRICATED | <input type="checkbox"/> DRY |
| <input type="checkbox"/> T 89 / B | <input type="checkbox"/> T 90 / B | <input type="checkbox"/> T 89 / A | <input type="checkbox"/> T 125 / B |
| <input type="checkbox"/> | | | |

SAFETY GEAR USE (*)

CAR SLING COUNTERWEIGHT SLING

RATED LOAD (*)

320 kg 450 kg 600 kg
 800 kg 1050 kg Kg

O.S.GOVERNOR POSITION

FRONT / LEFT BACK / LEFT FRONT / RIGHT
 BACK / RIGHT

TOTAL LOAD (*)

P + Q / F MAX. Kg

ROPE DIAMETER

6mm 6,5 mm 8 mm mm

RATED SPEED (*)

1,00 m/s 1,60 m/s m/s

DISTANCE GUIDE RAIL - ROPE / AK

250 mm 350 mm mm

TRIPPING SPEED (*)

1,25 m/s 2,00 m/s m/s

OPTIONAL REQUESTS

SAFETY GEAR SWITCH SYNCHRONISATION ROD
 SYNCHRONISATION ROPE HITCH

DISTANCE BETWEEN GUIDES / DBG (*)

1030 mm 1130 mm 1230 mm
 1330 mm 1430 mm mm

DBG : mm AK : mm

HOUSING

WITHOUT STANDARD

PACKING STANDARD CRATE

IN CASE SELECTION OF THE SAFETY GEAR IS REQUESTED TO BE DONE BY MARGALIFT, ALL INSTALLATION DATA MARKED WITH (*) SHOULD BE FILLED.

NOTES

.....

.....

.....

AREA RESERVED FOR WITTUR TR USE ONLY

..... can be delivered in a OFFER NO.

PRODUCTION SALES
 STAMP / DATE STAMP / DATE

CUSTOMER STAMP / SIGNATURE